9013GHG2S6J30

Square D Pumptrol, pressure switch 480 VAC 10 A g special





Main	
Device short name	G
Enclosure type	Standard environment enclosure indoor
Product Specific Application	Control electrically driven water pumps and air compressors

Square D Pumptrol

Standard

Complementary

Complementary	
Adjustable range on rising pressure	65200 psi (448.161378.95 kPa)
Approximate adjustable differential	2040 psi (137.90275.79 kPa)
Depth	3.68 in (93.47 mm)
Electrical connection	Screw clamp terminal
Fixing Mode	By brackets
Fluid connection type	0.25 inch NPSF internal
Height	5.72 in (145.29 mm)
Material	Zinc plated steel flange
Materials in contact with fluid	Nitrile (Buna-N) diaphragm
Maximum pressure	300 psig
Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 3 Hp 115 V AC, 3 phase 3 Hp 230 V AC, 1 phase 5 Hp 230 V AC, 3 phase 5 Hp 460/575 V AC, 1 phase 5 hp 460/575 V AC, 3 phase
Number of poles	2
Permissible voltage	575 V AC
Pressure actuator	Diaphragm
Pressure setting range	80100 psi (551.58689.48 kPa)
Product Weight	2.25 lb(US) (1.02 kg)
Range on decreasing pressure	40170 psi (275.791172.11 kPa)
Switch function	DPST
Width	3.44 in (87.38 mm)

Range of Product

Switch application

Environment

NEMA Degree of Protection	NEMA 1
Product Certifications	CSA file LR25490 UL listed file E12158 CCN NKPZ

Ordering and shipping details

Category	21536-9013 G COMMERCIAL PRESSURE SWITCH
Discount Schedule	CP7G
GTIN	785901559771
Returnability	Yes
Country of origin	MX

Packing Units

PCE	
1	
5.51 in (14.0 cm)	
4.80 in (12.2 cm)	
7.99 in (20.3 cm)	
34.08 oz (966.2 g)	
	1 5.51 in (14.0 cm) 4.80 in (12.2 cm) 7.99 in (20.3 cm)

Offer Sustainability

onor odotamasinty	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	[™] End Of Life Information

Contractual warranty

Warranty	18 months