9013GHG5S2J62

Square D Pumptrol, pressure switch 480 VAC 10 A g special





Main	
Device short name	G
Enclosure type	Standard environment enclosure indoor
Product Specific Application	Control electrically driven water pumps and air compressors

Square D Pumptrol

Standard

Complementary

Complementary		
Adjustable range on rising pressure	80250 psi (551.581723.69 kPa)	
Approximate adjustable differential	2445 psi (165.47310.26 kPa)	
Depth	3.68 in (93.47 mm)	
Electrical connection	Screw clamp terminal	
Fixing Mode	By brackets	
Fluid connection type	0.25 inch NPSF internal	
Height	5.72 in (145.29 mm)	
Material	Zinc plated steel flange	
Materials in contact with fluid	Nitrile (Buna-N) diaphragm	
Maximum pressure	300 psig	
Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 3 Hp 115 V AC, 3 phase 3 Hp 230 V AC, 1 phase 5 Hp 230 V AC, 3 phase 5 Hp 460/575 V AC, 1 phase 5 hp 460/575 V AC, 3 phase	
Number of poles	2	
Permissible voltage	575 V AC	
Pressure actuator	Diaphragm	
Pressure setting range	140175 psi (965.271206.58 kPa)	
Product Weight	2.25 lb(US) (1.02 kg)	
Range on decreasing pressure	32215 psi (220.631482.37 kPa)	
Switch function	DPST	
Width	3.44 in (87.38 mm)	

Range of Product

Switch application

Environment

NEMA Degree of Protection	NEMA 1
Product Certifications	UL listed file E12158 CCN NKPZ CSA file LR25490

Ordering and shipping details

Category	21536-9013 G COMMERCIAL PRESSURE SWITCH
Discount Schedule	CP7G
GTIN	785901163480
Returnability	No
Country of origin	MX

Packing Units

PCE	
1	
5.30 in (13.462 cm)	
4.80 in (12.192 cm)	
8.10 in (20.574 cm)	
34.40 oz (975.224 g)	
	1 5.30 in (13.462 cm) 4.80 in (12.192 cm) 8.10 in (20.574 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₽¥Yes
Environmental Disclosure	☑ Product Environmental Profile
Circularity Profile	☑ End Of Life Information

Contractual warranty

Warranty	18 months