Product data sheet Characteristics

9007AW36

Limit switch, 9007, 600 VAC 15amp aw +options



Main Range of Product 9007 Series name Heavy duty Product or Component Type Device short name 9007AW Product Specific Application Body type Plug-in

Compl	lementary
-------	-----------

Complementary	
Mounting Mode	Surface mounting
Operator profile	Plunger head
Material	Metal
Body Material	Cast zinc
Operator material	Cast zinc
Fixing Mode	By the body
Movement of operating head	Linear
Type of operator	Spring return roller plunger steel with micrometer adjustment
Switch actuation	By 30° cam
Type of approach	Traverse approach, 2 directions
Electrical connection	12 screw-clamp terminals AWG 22AWG 12)
Cable entry	1 entry for 1/2" - 14 NPT ANSI B1.20.1
Number of poles	1
Contacts type and composition	NC-NO SPDT-DB
Contact form	Form Z
Contact operation	Snap action
Number of steps	1
Contacts material	Silver contacts
Positive opening	Without
Terminals description ISO n°1	(3-4)NO (1-2)NC
Minimum force for tripping	3 lbf
Repeat accuracy	+/- 0.001 in
[le] rated operational current	5 A 600 V AC, A600 NEMA rating designation 6 A 480 V AC, A600 NEMA rating designation 10 A 240 V AC, A600 NEMA rating designation 15 A 120 V AC, A600 NEMA rating designation 0.02 A 600 V DC 0.2 A 250 V DC 0.5 A 125 V DC
[Ithe] conventional enclosed thermal current	15 A
[Ui] rated insulation voltage	600 V 3)UL 508 contact block 600 VCSA C22.2 No 14 contact block
Width	2.53 in (64.26 mm)
Height	3.68 in (93.47 mm)
Depth	1.44 in (36.58 mm)
Product Weight	1.25 lb(US) (0.57 kg)

Environment

NEMA degree of protection	NEMA 1 Nema type 250
	NEMA 2 Nema type 250
	NEMA 4 Nema type 250
	NEMA 12 Nema type 250
	NEMA 13 Nema type 250
IP degree of protection	IP65 conforming to IEC 60529
Ambient Air Temperature for Operation	0185 °F (-1885 °C)
Ambient Air Temperature for Storage	0185 °F (-1885 °C)
Protective treatment	Epoxy powder coat

Ordering and shipping details

0 11 0	
Category	21496-9007 AW PRECISION LIMIT SWITCHES
Discount Schedule	DS1
GTIN	785901804437
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.80 in (7.112 cm)
Package 1 Width	5.20 in (13.208 cm)
Package 1 Length	1.70 in (4.318 cm)
Package 1 Weight	20.00 oz (566.991 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	6.20 in (15.748 cm)
Package 2 Width	7.40 in (18.796 cm)
Package 2 Length	7.80 in (19.812 cm)
Package 2 Weight	12.55 lb(US) (5.693 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
• • •	