Product data sheet Characteristics

9007MS04S0102

Limit switch, 9007, 240 VAC 10amp ms +options



Main

Range of Product	9007
Series name	Miniature potted
Product or Component Type	Limit switch
Device short name	9007MS/ML
Sensor design	Miniature
Body type	Fixed
Head type	Rotary head
Material	Metal
Body Material	Cast zinc
Number of poles	1

Complementary

Complementary	
Fixing Mode	By the body
Movement of operating head	Rotary
Type of operator	Spring return without operating lever -
Type of approach	Lateral approach, 2 directions
Switch actuation	From left and right CW and CCW
Contacts type and composition	NC-NO
Switch Function	SPDT
Contact form	Form C
Contacts material	Silver contacts
Contact operation	Snap action
Positive opening	Without
Electrical connection	Pre-wired cable bottom
Type of cable	SJTO AWG 16), 3 ft (0.91 m), Yellow
Terminals description ISO n°1	(Red)NC (Green-yellow)Gnd (Black)Com (white)NO
Wire insulation material	PVC
Minimum torque for tripping	48 ozf.in
Maximum actuation speed	130 Ft/Min with 30° cam angle, levers only 90 ft/min with 45° cam angle, levers only
Tripping angle	35 °
Maximum displacement angle	70 °
[le] rated operational current	6 A 120 V AC, A300 NEMA rating designation 3 A 240 V AC, A300 NEMA rating designation 5 A 28 V DC
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	300 V 3)UL 508 300 V 3)CSA C22.2 No 14
Electrical durability	100000 cycles
Mechanical durability	10000000 cycles
Marking	CSA UL CE
Sale per indivisible quantity	1
Height	2.49 in (63.25 mm)

Width	1.56 in (39.62 mm)
Depth	0.62 in (15.75 mm)
Product Weight	1.2 lb(US) (0.54 kg)
T	
Environment Shock resistance	35 gn 9 ms IEC 60068-2-27
Vibration resistance	10 gn 751200 Hz)IEC 60068-2-6
NEMA degree of protection	- · · · · · · · · · · · · · · · · · · ·
NEIWA degree of protection	NEMA 1 Nema type 250 NEMA 2 Nema type 250 NEMA 4 Nema type 250 NEMA 6 Nema type 250
ID dograp of protection	NEMA 6P Nema type 250
IP degree of protection	IP67 conforming to IEC 60529 -40220 °F (-40104 °C)
Ambient Air Temperature for Operation	
Ambient Air Temperature for Storage Protective treatment	-40220 °F (-40104 °C)
Product Certifications	Epoxy powder coat UL
i roduci Oettiiications	CE CSA
Standards	LR 25490 Class 32 11 03 E78403
Ordering and shipping details Category	22431-LIMIT SWITCHES,TYPE 9007MS
Discount Schedule	DS1
GTIN	785901398998
Returnability	No
Country of origin	MX
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.81 in (9.677 cm)
Package 1 Width	1.50 in (3.81 cm)
Package 1 Length	9.68 in (24.581 cm)
Package 1 Weight	19.20 oz (544.311 g)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	EREACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
	- · · · · · · · · · · · · · · · · · · ·

18 months

Contractual warranty

Warranty