## Product data sheet Characteristics

# 9013GHG2S6J30X

# Square D Pumptrol, pressure switch 480 VAC 10 A g special





Main	
Device short name	G
Enclosure type	Standard environment enclosure indoor
Factory modification	2-way pressure release valve
Product Specific Application	Control electrically driven water pumps and air compressors

Square D Pumptrol

Standard

#### Complementary

65200 psi (448.161378.95 kPa)
2040 psi (137.90275.79 kPa)
3.68 in (93.47 mm)
Screw clamp terminal
By brackets
0.25 inch NPSF internal
5.72 in (145.29 mm)
Zinc plated steel flange
Nitrile (Buna-N) diaphragm
300 psig
2 Hp 115 V AC, 1 phase 3 Hp 115 V AC, 3 phase 3 Hp 230 V AC, 1 phase 5 Hp 230 V AC, 3 phase 5 Hp 460/575 V AC, 1 phase 5 hp 460/575 V AC, 3 phase
2
575 V AC
Diaphragm
80100 psi (551.58689.48 kPa)
2.25 lb(US) (1.02 kg)
40170 psi (275.791172.11 kPa)
DPST
3.44 in (87.38 mm)

Range of Product

Switch application

#### Environment

NEMA Degree of Protection	NEMA 1
Product Certifications	CSA file LR25490 UL listed file E12158 CCN NKPZ

## Ordering and shipping details

Category	21536-9013 G COMMERCIAL PRESSURE SWITCH
Discount Schedule	CP7G
GTIN	785901560074
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	12.40 in (31.484 cm)	
Package 1 Width	4.88 in (12.395 cm)	
Package 1 Length	31.48 in (79.969 cm)	
Package 1 Weight	2.25 lb(US) (1.021 kg)	

# Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS  Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	<sup>™</sup> End Of Life Information	

### Contractual warranty

Warranty	18 months