



## Main

|                                    |                                  |
|------------------------------------|----------------------------------|
| Range of Product                   | Telemecanique Cabling components |
| Accessory / separate part category | Cabling accessory                |
| Accessory / Separate Part Type     | Pre-wired connectors             |
| Series name                        | General purpose                  |

## Complementary

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Electrical connection          | Straight female connector 1/2"20 UNF, 3 pins |
| Cable connector fixing         | Screw-on                                     |
| Collar material                | Metal                                        |
| Status LED                     | Without                                      |
| Cable length                   | 16.40 ft (5 m)                               |
| Cable outer diameter           | 0.20 in (5.2 mm)                             |
| Cable composition              | 3 x 0.34 mm <sup>2</sup>                     |
| Wire insulation material       | PVC                                          |
| [Ue] rated operational voltage | 250 V AC<br>300 V DC                         |
| Line Rated Current             | 4 A                                          |
| Contact resistance             | 5000 µOhm                                    |
| Minimum insulating resistance  | 1 GΩ                                         |
| Product Weight                 | 0.77 lb(US) (0.35 kg)                        |

## Environment

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| IP Degree of Protection               | IP67<br>IP65                      |
| Product Certifications                | cULus                             |
| Ambient air temperature for operation | -13...176 °F (-25...80 °C) static |
| Ambient Air Temperature for Storage   | -13...176 °F (-25...80 °C)        |

## Ordering and shipping details

|                   |                      |
|-------------------|----------------------|
| Category          | 22483-MACHINE CABLES |
| Discount Schedule | DS3                  |
| GTIN              | 3389119073356        |
| Returnability     | Yes                  |
| Country of origin | CZ                   |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 3.15 in (8.0 cm)       |
| Package 1 Width              | 1.97 in (5.0 cm)       |
| Package 1 Length             | 5.91 in (15.0 cm)      |
| Package 1 Weight             | 6.84 oz (194.0 g)      |
| Unit Type of Package 2       | S02                    |
| Number of Units in Package 2 | 20                     |
| Package 2 Height             | 5.91 in (15.0 cm)      |
| Package 2 Width              | 11.81 in (30.0 cm)     |
| Package 2 Length             | 15.75 in (40.0 cm)     |
| Package 2 Weight             | 9.28 lb(US) (4.209 kg) |


## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                                                                                                 |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                                                                    |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                                                                                               |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                                                                                                               |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Dimensions




L : Length of cable  
(1) 1/2"-20UNF

---

## Connections and Schemes

---

### Connectors



GN : Green  
RD/ Red / White  
WH :  
RD/ Red / Black  
BK :