ZCEF0

Limit switch head, Limit switches XC Standard, ZCE, M12 metal end plunger





Main

Series name Standard format Product or Component Type Limit switch head Device short name ZCE Head type M12 plunger head Product Compatibility XCKT XCKP XCMD XCKD Associated body ZCMD29C12 ZCMD81L5 ZCMD39L5 ZCMD39L5 ZCMD39L5 ZCMD39L5 ZCMD39L5 ZCMD37L2 ZCMD69C12 ZCMD39L2 ZCMD39L2 ZCMD39L1 ZCMD25L1 ZCMD25L1 ZCMD25L1 ZCMD25L1 ZCMD25L1 ZCMD41L2 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L5 ZCMD21C12 ZCMD29L5 ZCMD21C12 ZCMD261C12 ZCMD261C12 ZCMD261C12 ZCMD81L2 ZCMD29L5 ZCMD37L1 ZCMD29L5 ZCMD37L1 ZCMD29L5 ZCMD37L1 ZCMD29L5 ZCMD81L1 ZCMD25L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L1 ZCMD21L1 ZCMD21L08U78 Movement of operating head Linear Type of operator End plunger spring return metal Type of approach Vertical approach, 1 direction	Range of Product	Telemecanique Limit switches XC Standard		
Device short name ZCE	Series name	Standard format		
Product Compatibility	•	Limit switch head		
Product Compatibility XCKT XCKP XCMD XCKD XCKD XCMD XCKD Associated body ZCMD29C12 ZCMD81L5 ZCMD39L5 ZCMD39L5 ZCMD37L2 ZCMD69C12 ZCMD37L5 ZCMD21L08R12 ZCMD39L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L1 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD21C12 ZCMD21L5 ZCMD21L5 ZCMD21L2 ZCMD21C12 ZCMD81L2 ZCMD21L2 ZCMD29L5 ZCMD21L2 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L1 ZCMD25L2 ZCMD25L2 ZCMD25L2 ZCMD29L1 ZCMD25L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD29L2 ZCMD21L1 ZCMD21L1 ZCMD21L08U78 Movement of operating head Linear head plunger spring return metal Type of operator End plunger spring return metal	Device short name	ZCE		
XCKP XCMD XCKD XCKD39L5 XCMD39L5 XCMD37L2 XCMD69C12 XCMD37L5 XCMD21L08R12 XCMD25L1 XCMD25L1 XCMD25L1 XCMD25L1 XCMD25L1 XCMD29L1 XCMD29L1 XCMD29L1 XCMD29L5 XCMD41L5 XCMD21L5 XCMD41L5 XCMD25L5 XCMD21C12 XCMD21C12 XCMD21L2 XCMD21L2 XCMD21L2 XCMD21L2 XCMD21L1 XCMD25L5 XCMD37L1 XCMD25L5 XCMD37L1 XCMD25L2 XCMD29L1 XCMD25L2 XCMD29L2 XCMD29L2 XCMD29L2 XCMD29L2 XCMD29L2 XCMD21L1 XCMD25L2 XCMD21L1 XCMD25L2 XCMD21L1 XCMD25L2 XCMD21L08U78 XCMD21L08U78 XCMD21L08U78 XCMD21L08U78 XCMD21L08U78 XCMD21C08U78 X	Head type	M12 plunger head		
ZCMD81L5 ZCMD39L5 ZCMD37L2 ZCMD69C12 ZCMD37L5 ZCMD21L08R12 ZCMD39L1 ZCMD25L1 ZCMD25L1 ZCMD41L2 ZCMD41L2 ZCMD41L5 ZCMD29L1 ZCMD29L1 ZCMD21L5 ZCMD21L5 ZCMD21C12 ZCMD21C12 ZCMD21C12 ZCMD21L2 ZCMD21L2 ZCMD21L2 ZCMD21L2 ZCMD21L2 ZCMD21L1 ZCMD21L08U78 Movement of operating head Type of operator End plunger spring return metal		XCKP XCMD		
Type of operator End plunger spring return metal	Associated body	ZCMD81L5 ZCMD39L5 ZCMD37L2 ZCMD69C12 ZCMD37L5 ZCMD21L08R12 ZCMD39L1 ZCMD39L1 ZCMD25L1 ZCMD41L2 ZCMD61M12 ZCMD29L1 ZCMD21L5 ZCMD21L5 ZCMD21L5 ZCMD21L5 ZCMD21C12 ZCMD81L2 ZCMD81L2 ZCMD21L2 ZCMD29L5 ZCMD21L2 ZCMD29L5 ZCMD21L1 ZCMD25L2 ZCMD21L1 ZCMD21L1		
Type of operator End plunger spring return metal	Movement of operating			
Type of approach Vertical approach, 1 direction	Type of operator	End plunger spring return metal		
	Type of approach	Vertical approach, 1 direction		

Complementary

Positive opening	With	
		- 8
Environment		, in the second

Ambient			t /	Air ⁻			Temperat					tu	ture				
	=									-					ī		

Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22413-LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	Т
GTIN	3389110190908
Returnability	Yes
Country of origin	ID

Packing Units

PCE	
1	
0.59 in (1.5 cm)	
1.30 in (3.3 cm)	
0.59 in (1.5 cm)	
1.09 oz (31.0 g)	
	1 0.59 in (1.5 cm) 1.30 in (3.3 cm) 0.59 in (1.5 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Contraction Warranty	ontraction warranty					
Warranty	18 months					