# Product data sheet Characteristics

## XS1M18DA9AV

Inductive sensor XS1 M18, L80mm, NO or NC, 12...48VDC, 100mA, cable 5m





#### Main

Telemecanique Inductive proximity sensors XS
General purpose
Inductive proximity sensor
XS1
Cylindrical M18
Fixed
Flush mountable
Metal
Discrete
2-wire
0.20 in (5 mm)
1 NO or 1 NC programmable
DC
PNP and NPN
Cable
16.40 ft (5 m)
1248 V DC reverse polarity protection
<= 100 mA overload and short-circuit protection

#### Complementary

Thread type	M18 x 1
Detection face	Frontal
Front material	PPS
Enclosure Material	Nickel Plated Brass
Operating zone	0.000.16 in (04 mm)
Differential travel	115% of Sr
Cable composition	3 x 0.34 mm²
Wire insulation material	PVC
Status LED	Output state 1 LED yellow)
Supply voltage limits	1036 V DC
Maximum voltage drop	<2.6 V closed)
Current consumption	010 mA no-load
Maximum delay first up	5 ms
Maximum delay response	0.15 ms
Maximum delay recovery	0.35 ms
Marking	CE UKCA
Threaded length	2.76 in (70 mm)
Length	3.15 in (80 mm)

## Environment

Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)
Vibration resistance	25 gn +/- 2 mm 1055 Hz)IEC 60068-2-6
Shock resistance	50 gn 11 ms IEC 60068-2-27

## Ordering and shipping details

Category	22486-SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	3389110202229
Returnability	Yes
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.01 in (5.1 cm)
Package 1 Width	5.83 in (14.8 cm)
Package 1 Length	5.51 in (14.0 cm)
Package 1 Weight	8.54 oz (242.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	22
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	14.37 lb(US) (6.519 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

### Contractual warranty

Warranty	18 months