Product data sheet Characteristics

9007AO1

Snap basic limit switch, 9007, 600 VAC 15amp ao +options



| Main | |
|------------------------------|-------------------------|
| Range of Product | 9007 |
| Series name | Heavy duty |
| Product or Component Type | Snap basic limit switch |
| Device short name | 9007AO/CO |
| Body type | Fixed |
| | |

| Comp | lemen ⁻ | tarv |
|------|--------------------|------|
| | | |

| Mounting Mode | - |
|--|---|
| Operator profile | Plunger head |
| Material | Metal |
| Body Material | Cast zinc |
| Operator material | Cast zinc |
| Fixing Mode | By the body |
| Movement of operating head | Linear |
| Type of operator | Spring return plunger plastic with thermoplastic end |
| Switch actuation | On end |
| Type of approach | Vertical approach, 1 direction |
| Electrical connection | 12 6 binder head screw terminals AWG 22AWG 14) |
| Number of poles | 1 |
| Contacts type and composition | NC-NO SPDT-DB |
| Contact form | Form Z |
| Contact operation | Snap action |
| Number of steps | 1 |
| Contacts material | Silver contacts |
| Positive opening | Without |
| Terminals description ISO n°1 | (1-2)NC |
| Minimum force for tripping | 0.44 lbf |
| Maximum force for tripping | 0.69 lbf |
| [le] rated operational current | 5 A 600 V AC, A600 NEMA rating designation 6 A 480 V AC, A600 NEMA rating designation 10 A 240 V AC, A600 NEMA rating designation 15 A 120 V AC, A600 NEMA rating designation 0.1 A 250 V DC 0.25 A 125 V DC |
| [Ithe] conventional enclosed thermal current | 15 A |
| [Ui] rated insulation voltage | 600 V 3)UL 508 contact block 600 VCSA C22.2 No 14 contact block |
| Width | 0.83 in (21.08 mm) |
| Height | 2.5 in (63.50 mm) |
| Depth | 1.03 in (26.16 mm) |
| Product Weight | 0.1 lb(US) (0.05 kg) |

Environment

| NEMA degree of protection | NEMA 1 Nema type 250 |
|---------------------------------------|------------------------------|
| IP degree of protection | IP20 conforming to IEC 60529 |
| Ambient Air Temperature for Operation | -20185 °F (-2985 °C) |
| Ambient Air Temperature for Storage | -20185 °F (-2985 °C) |

Ordering and shipping details

| Category | 21491-9007 A SNAP SWITCHES |
|-------------------|----------------------------|
| Discount Schedule | DS1 |
| GTIN | 785901759034 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| r doming office | |
|------------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 0.91 in (2.3 cm) |
| Package 1 Width | 4.02 in (10.2 cm) |
| Package 1 Length | 5.98 in (15.2 cm) |
| Package 1 Weight | 1.44 oz (40.8 g) |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 100 |
| Package 2 Height | 5.20 in (13.208 cm) |
| Package 2 Width | 9.70 in (24.638 cm) |
| Package 2 Length | 11.00 in (27.94 cm) |
| Package 2 Weight | 9.27 lb(US) (4.205 kg) |
| Unit Type of Package 3 | PAL |
| Number of Units in Package 3 | 2000 |
| Package 3 Height | 40.00 in (101.6 cm) |
| Package 3 Width | 40.00 in (101.6 cm) |
| Package 3 Length | 48.00 in (121.92 cm) |
| Package 3 Weight | 180.00 lb(US) (81.647 kg) |
| | |

Offer Sustainability

| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov | |
|----------------------------|---|--|
| REACh Regulation | REACh Declaration | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) | |
| Mercury free | Yes | |
| RoHS exemption information | ₫Yes | |

Contractual warranty

| Warranty | 18 months | |
|----------|-----------|--|