Product data sheet Characteristics

9007FA3

NEMA limit switch, 9007C, 304 steel spring rod lever arm, 12 inch rod



-	
壨	
単	

Main	
Range of Product	9007
Series name	Heavy duty
Product or Component Type	Limit switch lever
Device short name	9007C
Associated head	9007C 9007A 9007T5 9007N 9007T10 9007B
Associated complete product	9007C 9007AW
Movement of operating head	Rotary
Type of operator	Steel spring return spring rod lever 12 in (304.80 mm)
Type of approach	Lateral approach
Positive opening	Without

Complementary

Switch actuation	By any moving part
Product Weight	0.1 lb(US) (0.05 kg)

Environment

Ambient Air Temperature for Operation	-20185 °F (-2985 °C)
Ambient Air Temperature for Storage	-20185 °F (-2985 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	21493-9007 ARMS FOR AW,C
Discount Schedule	DS1
GTIN	785901742630
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Office Type of Fackage 1	FOL
Number of Units in Package 1	1
Package 1 Height	0.50 in (1.27 cm)
Package 1 Width	1.00 in (2.54 cm)
Package 1 Length	12.80 in (32.512 cm)
Package 1 Weight	2.40 oz (68.039 g)
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)

Package 2 Length	15.75 in (40.0 cm)	
Package 2 Weight	16.12 lb(US) (7.313 kg)	
Offer Sustainability		
Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Contraction Warranty		
Warranty	18 months	