XZCP0666L2

Pre wired connectors XZ, elbowed female, M8, 3 pins, cable PUR 2 m





Main	
Range of Product	Telemecanique Cabling components
Accessory / separate part category	Cabling accessory
Accessory / Separate Part Type	Pre-wired connectors
Series name	General purpose

Complementary

Complementary		
Electrical connection	Elbowed female connector M8, 3 pins	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	6.56 ft (2 m)	
Cable outer diameter	0.20 in (5.2 mm)	
Cable composition	3 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	60 V AC 75 V DC	
Line Rated Current	4 A	
Contact resistance	5000 μOhm	
Minimum insulating resistance	1 GΩ	
Product Weight	0.22 lb(US) (0.1 kg)	

Environment

LIMIOIIIICIIL		
IP Degree of Protection	IP65 IP67 IP69K	
Product Certifications	cULus	
Ambient air temperature for operation	-40176 °F (-4080 °C) static 23176 °F (-580 °C) flexing	
Ambient Air Temperature for Storage	-40176 °F (-4080 °C)	

Ordering and shipping details

22483-MACHINE CABLES
DS3
3389110762778
Yes
CZ

Packing Units

r doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	6.30 in (16.0 cm)
Package 1 Length	5.91 in (15.0 cm)
Package 1 Weight	1.98 oz (56.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	5.94 lb(US) (2.695 kg)


Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Contraction Warranty	
Warranty	18 months


Dimensions



L: Lenght of cable

Connections and Schemes

Connector



BU : Blue BN : Brown BK : Black