Product data sheet Characteristics

XCSL764F3

Interlock switch 300 VAC 10as XCSL





Main

Device short name	XCSL
Enclosure type	Water resistant enclosure indoor/outdoor Dustproof enclosure indoor/outdoor Ice/sleet proof enclosure indoor/outdoor

Complementary

Complementary		
Line Rated Current	10 A	
[Us] rated supply voltage	110 V AC	
Actuator	Key	
Contact operation	Slow-break, break before make	
Contacts type and composition	1 NO staggered 2 NC	
Depth	1.73 in (43.94 mm)	
Enclosure material	metal	
Height	7.64 in (194.06 mm)	
Installation direction	Electromagnet connection left Actuator supply right	
Key locking position	Front	
Locking options description	With locking of actuator, unlocking by key operated lock	
Number of poles	3	
Permissible voltage	300 V AC	
Pilot light	LED orange	

Environment

Ambient Air Temperature for Operation	-13158 °F (-2570 °C)	
IP Degree of Protection	IP67	
NEMA Degree of Protection	NEMA 1/2/3/4/12	

Ordering and shipping details

Category	22411-LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	Т
GTIN	3389118074385
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.05 in (5.2 cm)
Package 1 Width	2.44 in (6.2 cm)
Package 1 Length	11.02 in (28.0 cm)
Package 1 Weight	34.57 oz (980.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	22.61 lb(US) (10.255 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------