Product data sheet Characteristics

ZCKL1H7

Limit switch body, Limit switches XC Standard, ZCKL, 1NC+1 NO, snap action, 1/2"NPT





Main

Widin	
Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch body
Device short name	ZCKL
Body type	Fixed
Product Compatibility	XCKL
Associated head	ZCKD23 ZCKD239 ZCKD91 ZCKD59 ZCKD17 ZCKD41 ZCKD05 ZCKD21 ZCKD029 ZCKD16 ZCKD02 ZCKD06 ZCKD00 ZCKD06 ZCKD08 ZCKD10 ZCKD109 ZCKD109 ZCKD109 ZCKD15 ZCKD15 ZCKD08 ZCKD08
Body Material	Metal
Cable entry	1 entry tapped for 1/2" NPT conduit
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action
Number of steps	1 1 position
Contacts material	Silver plated contacts

Complementary

Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.342 x 1.5 mm ²
Positive opening	With
Minimum actuation speed	0.01 m/min
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	2.05 in (52 mm)
Height	2.83 in (72 mm)

Depth	1.18 in (30 mm)	
Product Weight	0.46 lb(US) (0.21 kg)	
Terminals description ISO n°1	(23-24)NO (13-14)NO	
Environment		
IP Degree of Protection	IP66	
IK Degree of Protection	IK05	

-40...158 °F (-40...70 °C)

Standard environment

-13...158 °F (-25...70 °C) standard environment

Ordering	and	ohinning	dotoilo
CHOEFFICE	ancı	SHIDDHIO	CHAIS

Ambient air temperature for operation

Ambient Air Temperature for Storage

Environmental characteristic

Category	22416-LIMIT SWITCHES,IEC,XCKL
Discount Schedule	Т
GTIN	3389110646146
Returnability	Yes
Country of origin	FR

Packing Units

· coming critic	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.42 in (3.6 cm)
Package 1 Width	2.48 in (6.3 cm)
Package 1 Length	4.02 in (10.2 cm)
Package 1 Weight	7.41 oz (210.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	19.00 lb(US) (8.619 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months	