Product data sheet Characteristics

XESP2051

Limit switch contact block, Limit switches XC Standard, XESP, 1C/O snap action, simultaneous, silver plated





Main

Telemecanique Limit switches XC Standard
Standard format
Limit switch contact block
XESP
1
Snap action, simultaneous
1 C/O

Complementary

Electrical connection Screw-clamp terminals 1 x 0.752 x 1.5 mm ²		
Contacts insulation form	Za	
Contacts material	Silver plated contacts	
Positive opening	Without	
Minimum actuation speed	0.01 mm/s	
Maximum resistance across terminals	25 mOhm IEC 60255-7 category 3	
Electrical durability	5000000 Cycles, DC-13 120 V, 4 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix 5000000 Cycles, DC-13 24 V, 10 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix 5000000 cycles, DC-13 48 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix 0	

Ordering and shipping details

<u></u>	
Category	22449-LIMIT SWITCHES,ACCESSORIES
Discount Schedule	T
GTIN	3389110645743
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.98 in (2.5 cm)	
Package 1 Width	2.76 in (7.0 cm)	
Package 1 Length	2.76 in (7.0 cm)	
Package 1 Weight	0.74 oz (21.0 g)	

Offer Sustainability

Warranty

Green Premium product	
WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Declaration	
Yes	
Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration	
Yes	
€Yes	
Product Environmental Profile	

18 months