Product data sheet Characteristics

ZCKS404

Limit switch body with spring return rotary head, Limit switches XC Standard, ZCKS, w/o op. lever, 2C/O, snap action, Pg13.5





Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch body with spring return rotary head
Device short name	ZCKS
Body type	Fixed
Product Compatibility	XCKS
Associated head	ZCKD59 ZCKD54 ZCKD33 ZCKD39 ZCKD34 ZCKD05 ZCKD01 ZCKD01 ZCKD49 ZCKD029 ZCKD91 ZCKD019 ZCKD08 ZCKD55 ZCKD06 ZCKD55 ZCKD06 ZCKD41 ZCKD02 ZCKD41 ZCKD02 ZCKD41 ZCKD02 ZCKD31 ZCKD81
Body Material	Plastic
Cable entry	1 entry tapped for Pg 13.5 cable gland
Number of poles	2
Contacts type and composition	2 C/O
Contact operation	Snap action
Number of steps	2 3 positions
Contacts material	Silver plated contacts

Complementary

Switch actuation	From left and right
Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.752 x 1.5 mm²
Positive opening	Without
Minimum actuation speed	0.01 m/min
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C

Width	1.57 in (40 mm)	
Height	2.87 in (73 mm)	
Depth	1.42 in (36 mm)	
Product Weight	0.18 lb(US) (0.08 kg)	
Terminals description ISO n°1	(13-14)NO (23-24)NO	

Environment

IP Degree of Protection	IP65	
IK Degree of Protection	IK03	
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Environmental characteristic	Standard environment	

Ordering and shipping details

0 11 0	
Category	22411-LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	Т
GTIN	3389110599688
Returnability	No
Country of origin	FR

Packing Units

r acking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.36 in (6 cm)
Package 1 Width	2.83 in (7.2 cm)
Package 1 Length	4.72 in (12 cm)
Package 1 Weight	5.78 oz (164 g)
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	7.92 lb(US) (3.591 kg)

Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Yes
€Yes
Product Environmental Profile
End Of Life Information

Contractual warranty

Warranty	18 months