## Product data sheet Characteristics

# ZCKL5

Limit switch body, Limit switches XC Standard, ZCKL, 1NC+1 NO, slow break, Cable gland include





#### Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch body
Device short name	ZCKL
Body type	Fixed
Product Compatibility	XCKL
Associated head	ZCKD16 ZCKD15 ZCKD41 ZCKD02 ZCKD05 ZCKD109 ZCKD81 ZCKD17 ZCKD10 ZCKD29 ZCKD29 ZCKD219 ZCKD219 ZCKD23 ZCKD21 ZCKD21 ZCKD21 ZCKD21 ZCKD21 ZCKD21 ZCKD21 ZCKD21
Body Material	Metal
Cable entry	1 tapped entry for Pg 13.5 cable gland (included)
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Slow-break, break before make
Number of steps	1 1 position
Contacts material	Silver plated contacts

#### Complementary

Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.52 x 2.5 mm <sup>2</sup>
Positive opening	With
Minimum actuation speed	6 m/min
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	2.05 in (52 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Height	2.83 in (72 mm)	
Depth	1.18 in (30 mm)	
Product Weight	0.46 lb(US) (0.21 kg)	
Terminals description ISO n°1	(21-22)NC (11-12)NC	

#### Environment

IP Degree of Protection	IP66	
IK Degree of Protection	IK05	
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Environmental characteristic	Standard environment	

### Ordering and shipping details

0 11 0	
Category	22416-LIMIT SWITCHES,IEC,XCKL
Discount Schedule	Т
GTIN	3389110646672
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.26 in (3.2 cm)
Package 1 Width	2.60 in (6.6 cm)
Package 1 Length	3.15 in (8.0 cm)
Package 1 Weight	7.94 oz (225.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	20.82 lb(US) (9.444 kg)

#### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

Warranty	18 months