Product data sheet Characteristics

ZCKS2

Limit switch body, Limit switches XC Standard, ZCKS, 2C/O, snap action, Pg13.5





Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch body
Device short name	ZCKS
Body type	Fixed
Product Compatibility	XCKS
Associated head	ZCKD08 ZCKD39 ZCKD019 ZCKD01 ZCKD05 ZCKD34 ZCKD33 ZCKD81 ZCKD41 ZCKD429 ZCKD49 ZCKD54 ZCKD54 ZCKD54 ZCKD54 ZCKD55 ZCKD55 ZCKD61
Body Material	Plastic
Cable entry	1 entry tapped for Pg 13.5 cable gland
Number of poles	2
Contacts type and composition	2 C/O
Contact operation	Snap action
Number of steps	1 1 position
Contacts material	Silver plated contacts

Complementary

Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.752 x 1.5 mm²
Positive opening	Without
Minimum actuation speed	0.01 m/min
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	1.57 in (40 mm)
Height	2.87 in (73 mm)

Depth	1.42 in (36 mm)	
Product Weight	0.18 lb(US) (0.08 kg)	
Terminals description ISO n°1	(11-12)NC (21-22)NC	
Environment		
IP Degree of Protection	IP65	
IV Dograp of Protection	IVO2	

IP Degree of Protection	IP65
IK Degree of Protection	IK03
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22411-LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	Т
GTIN	3389110645842
Returnability	No
Country of origin	FR

Packing Units

r doming office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.42 in (3.6 cm)
Package 1 Width	1.57 in (4.0 cm)
Package 1 Length	2.83 in (7.2 cm)
Package 1 Weight	3.00 oz (85.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	72
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	14.16 lb(US) (6.423 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Contractual warranty		
Warranty	18 months	