## Product data sheet Characteristics

# ZCMC21L5

Pre cabled connection, Limit switches XC Standard, ZCMC, 2 Poles, PvR, 5 m





#### Main

Range of Product	Telemecanique Limit switches XC Standard
Product or Component Type	Pre-cabled connection
Component name	ZCMC
Associated body	ZCMD21
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action

#### Complementary

Product Compatibility	XCMD21
Electrical connection	Cable
Cable length	16.40 ft (5 m)
Wire insulation material	PvR

### Ordering and shipping details

Category	22413-LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	Т
GTIN	3389110221725
Returnability	Yes
Country of origin	ID

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.18 in (3.0 cm)
Package 1 Width	7.28 in (18.5 cm)
Package 1 Length	7.87 in (20.0 cm)
Package 1 Weight	15.34 oz (435.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	25
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	19.30 lb(US) (8.753 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	200
Package 3 Height	27.56 in (70.0 cm)
Package 3 Width	23.62 in (60.0 cm)
Package 3 Length	31.50 in (80.0 cm)
Package 3 Weight	224.58 lb(US) (101.868 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

# Contractual warranty

	•
14/	40
vvarrantv	18 months