# Product data sheet Characteristics

## ZCMD21

Limit switch body, Limit switches XC Standard, ZCMD, 1NC+1 NO, silver, snap action





#### Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch body
Device short name	ZCMD
Design	Miniature
Body type	Plug-in body
Associated head	ZCE13 ZCEF2 ZCE63 ZCE27 ZCEH2 ZCEH2 ZCE10 ZCE01 ZCE01 ZCE66 ZCE66 ZCE64 ZCE62 ZCE02 ZCE02 ZCEH0 ZCEF0 ZCE05 ZCE05 ZCE05 ZCE05 ZCE65 ZCE67 ZCE08 ZCE07 ZCE08 ZCE07 ZCE14 ZCE11 ZCE24 ZCE28 ZCE21
Body Material	Zamak
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action

#### Complementary

Product Compatibility	XCMD	
Associated connection component	ZCMC21T2 ZCMC21L10 ZCMC21E3 ZCMC21E7 ZCMC21E5 ZCMC21L7 ZCMC21L7 ZCMC21T1 ZCMC21T1 ZCMC21L1 ZCMC21L1 ZCMC21L1 ZCMC21L1 ZCMC21L1 ZCMC21L1 ZCMC21L1 ZCMC21L1 ZCMC21L5 ZCMC21L5 ZCMC21L5	
Electrical connection	ZCMC21E10	
Electrical connection	Plug-in without pre-cabled connection	
Contacts insulation form	Zb	
Contacts material	Silver plated contacts	
Positive opening	With	
Minimum actuation speed	0.01 m/min	
Contact code designation	B300, AC-15 (Ue = 240 V), le = 1.5 A EN/IEC 60947-5-1 appendix A R300, DC-13 (Ue = 250 V), le = 0.1 A EN/IEC 60947-5-1 appendix A	
[Ui] rated insulation voltage	300 V 3)UL 508 400 V 3)IEC 60947-5-1 300 V 3)CSA C22.2 No 14	
Maximum resistance across terminals	25 mOhm IEC 60255-7 category 3	
[Uimp] rated impulse withstand voltage	4 KV IEC 60664 4 kV IEC 60947-1	
Short-circuit protection	6 A cartridge fuse gG	
Electrical durability	5000000 Cycles, DC-13 120 V, 1 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 3 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 2 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C	
Width	1.18 in (30 mm)	
Height	1.97 in (50 mm)	
Depth	0.63 in (16 mm)	

#### Environment

Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
-------------------------------------	----------------------	--

## Ordering and shipping details

Category	22413-LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	T
GTIN	3389110299069
Returnability	Yes
Country of origin	ID

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.70 in (1.778 cm)	
Package 1 Width	1.30 in (3.302 cm)	
Package 1 Length	2.00 in (5.08 cm)	
Package 1 Weight	2.02 oz (57.15 g)	
Unit Type of Package 2	P06	
Number of Units in Package 2	1280	
Package 2 Height	31.50 in (80.0 cm)	
Package 2 Width	31.50 in (80.0 cm)	
Package 2 Length	23.62 in (60.0 cm)	

Package 2 Weight	192.64 lb(US) (87.38 kg)
Unit Type of Package 3	S01
Number of Units in Package 3	40
Package 3 Height	5.91 in (15.0 cm)
Package 3 Width	5.91 in (15.0 cm)
Package 3 Length	15.75 in (40.0 cm)
Package 3 Weight	5.76 lb(US) (2.612 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

### Contractual warranty

Contraction warranty	
Warranty	18 months