Limit switch lever, Limit switches XC Standard, ZCY, forked arm with rollers 2 tracks





Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch lever
Device short name	ZCY
Product Compatibility	XCKT XCMD XCKP XCKD
Associated head	ZCE09
Movement of operating head	Rotary
Type of operator	Stay put forked arm with rollers stay put 2 tracks)
Tracks	21/35 mm XCMD 25/39 mm XCKD 25/39 mm XCKP 25/39 mm XCKT
Type of approach	Lateral approach

Complementary

Switch actuation	By specific cam
Positive opening	Without

Environment

Livilotimon	
Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient air temperature for storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22413-LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	Т
GTIN	3389110192049
Returnability	No
Country of origin	ID

Packing Units

1 doking Onits	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.59 in (1.5 cm)
Package 1 Width	2.36 in (6 cm)
Package 1 Length	1.85 in (4.7 cm)
Package 1 Weight	0.81 oz (23 g)
Unit Type of Package 2	BAG
Number of Units in Package 2	10
Package 2 Height	1.57 in (4 cm)
Package 2 Width	3.94 in (10 cm)
Package 2 Length	3.94 in (10 cm)
Package 2 Weight	8.29 oz (235 g)

Unit Type of Package 3	S01	
Number of Units in Package 3	200	
Package 3 Height	5.91 in (15 cm)	
Package 3 Width	5.91 in (15 cm)	
Package 3 Length	15.75 in (40 cm)	
Package 3 Weight	10.94 lb(US) (4.962 kg)	

Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
☑ REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Yes
₫Yes
Product Environmental Profile
End Of Life Information

Contractual warranty

Contraction Warranty	
Warranty	18 months