



### Main

|                              |                                                      |
|------------------------------|------------------------------------------------------|
| Range of Product             | Square D Pumptrol                                    |
| Pressure sensor name         | 9013FS                                               |
| Pressure sensor size         | 65 psi (448.16 kPa) 5...45 psi (34.47...310.26 kPa)) |
| Value of setting             | 40...60 psi                                          |
| Electrical circuit type      | Power circuit                                        |
| Product Specific Application | Control electrically driven water pumps              |
| Quantity per Set             | 1                                                    |
| Type of Packing              | Individual                                           |

### Complementary

|                                     |                                                                                                                                                                                                        |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pressure sensor type                | Electromechanical pressure switch                                                                                                                                                                      |
| Controlled fluid                    | Fresh water -22...257 °F (-30...125 °C))                                                                                                                                                               |
| Adjustable range on rising pressure | 20...65 psi (137.90...448.16 kPa)                                                                                                                                                                      |
| Approximate adjustable differential | 15...30 psi (103.42...206.84 kPa)                                                                                                                                                                      |
| Destruction pressure                | 220 psi (1516.85 kPa)                                                                                                                                                                                  |
| Pressure actuator                   | Diaphragm                                                                                                                                                                                              |
| Pressure switch type of operation   | Regulation between 2 thresholds                                                                                                                                                                        |
| Scale type                          | Adjustable differential                                                                                                                                                                                |
| Setting                             | Internal                                                                                                                                                                                               |
| Local display                       | Without                                                                                                                                                                                                |
| Contacts type and composition       | 2 NC, snap action, DPST-DB, Form YY                                                                                                                                                                    |
| Cable entry number                  | 2 0.88 in (22.35 mm) cable entries with 0.84 in across flats UL 508                                                                                                                                    |
| Electrical connection               | Screw-clamp terminals 10 AWG<br>Screw-clamp terminals 5.261 mm²                                                                                                                                        |
| Fluid connection type               | 0.25 inch NPT external UL 508                                                                                                                                                                          |
| Short-circuit protection            | 20 A cartridge fuse gG                                                                                                                                                                                 |
| Materials in contact with fluid     | Zinc plated steel or equivalent flange<br>Nitrile (Buna-N) or equivalent rubber diaphragm                                                                                                              |
| Material                            | Polypropylene Cover<br>Noryl thermoplastic resin or equivalent Cover                                                                                                                                   |
| Operating position                  | Any position                                                                                                                                                                                           |
| Motor power kW                      | 1.5 KW 2 hp)230 V AC, 1 phase<br>1.1 KW 1.5 hp)115 V AC, 1 phase<br>1.5 KW 2 hp)115 V AC, 3 phase<br>2.2 KW 3 hp)230 V AC, 3 phase<br>0.75 KW 1 hp)460 V AC, 3 phase<br>0.75 kW 1 hp)575 V AC, 3 phase |
| Electrical durability               | 100000 cycles 10 cyc/mn                                                                                                                                                                                |
| Mechanical durability               | 300000 cycles                                                                                                                                                                                          |
| Terminal block type                 | 4 terminals                                                                                                                                                                                            |
| Maximum operating rate              | 10 cyc/mn                                                                                                                                                                                              |
| [Ui] rated insulation voltage       | 575 V UL 508                                                                                                                                                                                           |
| Product Weight                      | 1 lb(US) (0.45 kg)                                                                                                                                                                                     |
| Repeat accuracy                     | +/- 3 %                                                                                                                                                                                                |
| Terminals description ISO n°1       | L2-T2<br>L1-T1                                                                                                                                                                                         |

|                      |                    |
|----------------------|--------------------|
| Width                | 2.78 in (70.61 mm) |
| Height               | 2.8 in (71.12 mm)  |
| Depth                | 3.76 in (95.50 mm) |
| Factory modification | -                  |

## Environment

|                                       |                                           |
|---------------------------------------|-------------------------------------------|
| Standards                             | NSF ANSI 61 Annex G<br>CE<br>UL 508       |
| Ambient Air Temperature for Operation | -33...257 °F (-36...125 °C)               |
| Ambient Air Temperature for Storage   | -33...257 °F (-36...125 °C)               |
| Protective treatment                  | None                                      |
| NEMA degree of protection             | NEMA 1 UL 50                              |
| IP degree of protection               | IP20 conforming to IEC 60529              |
| Product Certifications                | UL listed file E12158<br>CSA file LR25490 |

## Ordering and shipping details

|                   |                                        |
|-------------------|----------------------------------------|
| Category          | 21534-9013 FSG,FYG (INDIVIDUAL - CP7I) |
| Discount Schedule | CP7I                                   |
| GTIN              | 785901962076                           |
| Returnability     | Yes                                    |
| Country of origin | MX                                     |

## Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Number of Units in Package 1 | 1                        |
| Package 1 Height             | 10.16 in (25.806 cm)     |
| Package 1 Width              | 4.00 in (10.16 cm)       |
| Package 1 Length             | 25.81 in (65.548 cm)     |
| Package 1 Weight             | 13.12 oz (371.946 g)     |
| Unit Type of Package 2       | CAR                      |
| Number of Units in Package 2 | 50                       |
| Package 2 Height             | 8.50 in (21.59 cm)       |
| Package 2 Width              | 15.00 in (38.1 cm)       |
| Package 2 Length             | 21.00 in (53.34 cm)      |
| Package 2 Weight             | 42.45 lb(US) (19.255 kg) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                                                                                                 |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                                                                    |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                                                                                               |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                                                                                                               |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                                                                                                                     |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                                                                                                                                                                                                                                                                           |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|