



Main

| | |
|---------|-------------|
| Product | End tap box |
| Range | I-Line |

Complementary

| | |
|---------------------------|---|
| Rated Current | 1200 A copper |
| Rated Operational Voltage | 600 V AC/DC 50/60 Hz |
| Length | 29.14 in (740.16 mm) |
| Height | 28 in (711.20 mm) |
| Width | 11 in (279.40 mm) |
| Material | Copper busbar |
| I-LINE Value End | Bolt |
| Number of Phases | 3 phase |
| For Use with | Busbar trunking 1200 A copper |
| Protection Type | 50 percent capacity integral ground bus |
| Wiring Configuration | 4-wire |

Environment

| | |
|-----------|---|
| Standards | UL 857 CSA C22.2 No 27:1994 IEC 61439-6 |
|-----------|---|

Ordering and shipping details

| | |
|-------------------|--|
| Category | 20033-1200A CU FEEDER BUS IP54 THERMAL |
| Discount Schedule | PE8 |
| GTIN | 785901066323 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 29.13 in (74.0 cm) |
| Package 1 Width | 10.98 in (27.9 cm) |
| Package 1 Length | 27.99 in (71.1 cm) |
| Package 1 Weight | 167.00 lb(US) (75.75 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|