

# HEPD25W

Surge protection device, HEPD, 25kA, 120/240 V, 1 phase, 3 wire, SPD type 1, wholesale



## Main

Product	Surge protection device
Range	Square D
Device Short Name	HEPD
Type of Packing	Wholesale

## Complementary

Surge Current	25 kA per phase
Voltage Rating	120/240 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire (isolated ground)
MCOV	150 V
Nominal Discharge Current	10 kA
SCCR	22 kA
Local Signalling	1 LED green normal operation
Product destination	Load center
Input voltage	600 V L-N
Height	2.45 in (62.23 mm)
Width	2.89 in (73.41 mm)
Depth	2.06 in (52.32 mm)

## Environment

Enclosure Rating	NEMA 4X
------------------	---------

## Ordering and shipping details

Category	08461-SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	785901479758
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.30 in (8.382 cm)
Package 1 Width	4.10 in (10.414 cm)
Package 1 Length	5.60 in (14.224 cm)
Package 1 Weight	18.08 oz (512.565 g)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>