HOMT225240

Quad tandem circuit breaker, Homeline, 1 x 2 pole at 25A, 1 x 2 pole at 40A, 120/240VAC, 10kA AIR, plug in, UL



Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	25 A 40 A
Certifications	UL Listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Short Circuit Current Rating	10 kA
Number of Spaces	2.0
Circuit Breaker Type	Quad tandem
Ratings	HACR rated
Electrical Connection	Box lugs
Wire Size	1 x AWG 14AWG 8 (aluminium/copper) 1 x AWG 14AWG 6 (aluminium/copper)

Complementary

Tightening torque	35.4040.71 Lbf.In (4.04.6 N.m) 0.000.02 in² (2.510 mm²) (AWG 14AWG 6) 35.4040.71 lbf.in (4.04.6 N.m) 0.000.03 in² (2.520 mm²) (AWG 12AWG 6)
Height	3.13 in (79.50 mm)
Width	1.97 in (50.04 mm)
Depth	3.29 in (83.57 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)	

Ordering and shipping details

00046-HOM/T 15-30A 1P; 15-60A 2P	
DE3D	
785901970422	
No	
MX	
	DE3D 785901970422 No

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.15 in (8 cm)	
Package 1 Width	1.97 in (5 cm)	
Package 1 Length	3.31 in (8.4 cm)	
Package 1 Weight	16.00 oz (453.592 g)	

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₽¥Yes	