



### Main

Product Range	Type S
Component type	Push-button
Used with	Contactor starter

### Complementary

NEMA size	2 1 3 00 0
Marking	ON-OFF
Mounting Mode	Panel-mounted
Rated breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 0.6 A 600 V AC inductive control circuit UL 508 5 A 600 V AC resistive control circuit UL 508
Height	1.02 in (25.8 mm)
Width	2.58 in (65.5 mm)
Depth	24.00 in (609.6 mm)

### Environment

NEMA Degree of Protection	NEMA 1
Product Certifications	UL Listed UL Recognized CSA


### Ordering and shipping details

Category	21761-9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	785901721314
Returnability	No
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.90 in (4.826 cm)
Package 1 Width	3.90 in (9.906 cm)
Package 1 Length	5.80 in (14.732 cm)
Package 1 Weight	5.76 oz (163.293 g)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Under investigation
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------