



Main

Product	End tap box
Range	I-Line

Complementary

Rated Current	2500 A copper
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	39.38 in (1000.25 mm)
Height	28 in (711.20 mm)
Width	20.88 in (530.35 mm)
Material	Copper busbar
I-LINE Value End	Bolt
Number of Phases	3 phase
For Use with	Busbar trunking 2500 A copper
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	4-wire

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

Ordering and shipping details

Category	20041-2500A CU FEEDER BUS IP54 THERMAL
Discount Schedule	PE8
GTIN	785901182535
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.37 in (100.0 cm)
Package 1 Width	20.87 in (53.0 cm)
Package 1 Length	27.99 in (71.1 cm)
Package 1 Weight	240.00 lb(US) (108.862 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------