

# 9070MN250G0D1

Transformer disconnect, 250VA, 240x480VAC primary, 120VAC secondary, without outlet, compact Type 1

## Main

Product	Transformer Disconnect
Certifications	CSA UL Listed
Enclosure Type	NEMA 1 mini
Insulation Temperature	221 °F (105 °C)
Phase	1 phase
Primary Voltage	240 x 480 V
Power Rating	250 VA
Secondary Voltage	120 V
Temperature Rise	80 °C
Electrical Connection	Screw clamp terminals
Type	MN

## Ordering and shipping details

Category	21694-9070 SK
Discount Schedule	CP8
GTIN	785901746638
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.60 in (21.844 cm)
Package 1 Width	12.20 in (30.988 cm)
Package 1 Length	12.20 in (30.988 cm)
Package 1 Weight	21.00 lb(US) (9.525 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	18 months
----------	-----------