QOB320PL

Mini circuit breaker, QO, 20A, 3 pole, 240VAC, 10kA, Powerlink, bolt on mount



Main	
Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	240 V AC
Mounting Type	Bolt-on
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated

Box lugs

Complementary

Interrupt Rating	10 kA 240 V AC 50/60 Hz	
Number of Panel Spaces	3	
Provided Equipment	18 in (457.20 mm) lead	
Wire Size	AWG 12AWG 2 aluminium AWG 14AWG 2 copper	
Tightening Torque	35.40 lbf.in (4 N.m)	
Height	4.57 in (116 mm)	
Width	2.24 in (57 mm)	tion of the second of the seco
Depth	2.91 in (74 mm)	
Net Weight	1.21 lb(US) (0.549 kg)	

Electrical Connection

Environment

LITTION		
Certifications	UL Listed CSA	
Ambient Rating	104 °F (40 °C)	

Ordering and shipping details

Category	09650-POWERLINK QO(B)PL BREAKERS
Discount Schedule	DE8A
GTIN	785901095828
Returnability	No

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.40 in (6.096 cm)	
Package 1 Width	3.50 in (8.89 cm)	
Package 1 Length	5.50 in (13.97 cm)	
Package 1 Weight	1.21 lb(US) (0.549 kg)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	€Yes

Contractual warranty

Warranty	18 months	