



Main

Range of Product	Expansion Modules
Product or Component Type	I/O module
Range Compatibility	SCADAPack 47x SCADAPack 57x SCADAPack 500E

Complementary

Input type	Digital x16 Analog x6 Counter x8
Analogue input type	Voltage 0...5 V Voltage 1...5 V Current 0...20 mA Current 4...20 mA
Output type	8 digital
Power Consumption in W	1.1 W
Length	1.76 in (44.7 mm)
Width	5.93 in (150.5 mm)
Height	7.18 in (182.3 mm)

Environment

Marking	CE RCM
Product Certifications	CE[RETURN]CSA[RETURN]cCSAus HazLoc Class I Division 2 Group A[RETURN]cCSAus HazLoc Class I Division 2 Group B[RETURN]cCSAus HazLoc Class I Division 2 Group C[RETURN]cCSAus HazLoc Class I Division 2 Group D[RETURN]UL
Standards	FCC CFR 47 part 15, Subpart B ICES-003 UL 61010-2-201 UL 61010-1 CSA C22.2 No 61010-1 CSA C22.2 No 61010-1-12 IEC 61131-2
Pollution degree	2
Relative humidity	5...95 %
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C) -40...185 °F (-40...85 °C)
Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C) -40...316 °F (-40...158 °C)

Ordering and shipping details

Category	18270-TELEMETRY MISCELLANEOUS
Discount Schedule	TRSS
GTIN	3606489798260
Returnability	No
Country of origin	CA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.85 in (4.71 cm)
Package 1 Width	7.18 in (18.23 cm)
Package 1 Length	5.93 in (15.05 cm)
Package 1 Weight	1.76 lb(US) (0.8 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.