

9070SK1500G2D1

Transformer disconnect, 1500VA, 240x480VAC
primary, 120VAC secondary, without outlet,
Type 1

Main

Product	Transformer Disconnect
Certifications	CSA UL Listed
Enclosure Type	NEMA 1 standard
Insulation Temperature	356 °F (180 °C)
Phase	1 phase
Primary Voltage	240 x 480 V
Power Rating	1500 VA
Secondary Voltage	120 V
Temperature Rise	115 °C
Electrical Connection	Screw clamp terminals
Type	SK

Ordering and shipping details

Category	21694-9070 SK
Discount Schedule	CP8
GTIN	785901099505
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.50 in (41.91 cm)
Package 1 Width	18.50 in (46.99 cm)
Package 1 Length	24.50 in (62.23 cm)
Package 1 Weight	67.00 lb(US) (30.391 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------