



## Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Product or Component Type | Electrically Held Lighting Contactor |
| Range of Product          | 8903L                                |
| Control Circuit           | Separate control circuit             |

## Complementary

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Control Circuit Voltage         | 24 V AC 60 Hz                     |
| Inrush power in VA              | 180 VA 60 Hz                      |
| Hold-in power consumption in VA | 35 VA 60 Hz                       |
| Current Rating                  | 20 A tungsten<br>30 A fluorescent |
| Number of Poles                 | 8P 8 NO                           |
| Control Unit                    | No control units                  |
| Pilot Light                     | No indicator                      |
| Electrical Connection           | Screw-clamp terminals             |
| Height                          | 12.68 in (322 mm)                 |
| Depth                           | 6.02 in (153 mm)                  |
| Width                           | 7.80 in (198 mm)                  |

## Environment

|                        |                                    |
|------------------------|------------------------------------|
| Enclosure Type         | NEMA 1 painted sheet steel surface |
| Product Certifications | UL Listed<br>CSA                   |

## Ordering and shipping details

|                   |                       |
|-------------------|-----------------------|
| Category          | 21321-8903 L (NOT LX) |
| Discount Schedule | CP1                   |
| GTIN              | 785901022831          |
| Returnability     | No                    |
| Country of origin | MX                    |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 7.40 in (18.796 cm)    |
| Package 1 Width              | 8.20 in (20.828 cm)    |
| Package 1 Length             | 13.00 in (33.02 cm)    |
| Package 1 Weight             | 9.94 lb(US) (4.509 kg) |

## Offer Sustainability

|                             |                                                                                                                                 |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status    | Green Premium product                                                                                                           |
| REACH Regulation            | <a href="#"> REACH Declaration</a>             |
| REACH free of SVHC          | Yes                                                                                                                             |
| EU RoHS Directive           | Compliant <a href="#"> EU RoHS Declaration</a> |
| Toxic heavy metal free      | Yes                                                                                                                             |
| Mercury free                | Yes                                                                                                                             |
| China RoHS Regulation       | <a href="#"> China RoHS Declaration</a>        |
| RoHS exemption information  | <a href="#"> Yes</a>                           |
| Environmental Disclosure    | <a href="#"> Product Environmental Profile</a> |
| PVC free                    | Yes                                                                                                                             |
| Halogen content performance | Halogen free plastic parts product                                                                                              |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|