8940WF3S2V06H30

Pump Panel, NEMA Type S, Well Guard, oil field, Size 4, 135A, 100 HP, 200A fusible disconnect, Motor Logic SSOLR, 440/480 VAC 50/60 Hz coil, NEMA 3R



Main

Product	Well-Guard Control
Туре	S2
Device Application	Pumping

Complementary

Complementary	
Control Circuit Type	Common control circuit
Control Circuit Voltage	480 V AC 60 Hz 440 V AC 50 Hz
Line Rated Current	135 A
Number of Poles	3
Horsepower Rating	100 hp 480 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO)
Disconnect Type	Fusible disconnect switch
Associated fuse rating	400 A
Fuse type	H or K
Thermal overload type	Motor Logic solid state class 10/20
Protection Type	Overload Phase loss Phase unbalance
Device mounting	Surface
Electrical Connection	Screw terminal
NEMA size	4
Height	56.50 in (1435 mm)
Width	24.49 in (622 mm)
Depth	10.31 in (262 mm)

Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product Certifications	UL Listed NEMA

Ordering and shipping details

Category	21397-8940 WE,WF
Discount Schedule	CP1
GTIN	785901008828
Returnability	No
Country of origin	MX

Packing Units

PCE	
1	
56.50 in (143.5 cm)	
24.49 in (62.2 cm)	
10.31 in (26.2 cm)	
175.00 lb(US) (79.379 kg)	
	1 56.50 in (143.5 cm) 24.49 in (62.2 cm) 10.31 in (26.2 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
China RoHS Regulation	[™] China RoHS Declaration

Contractual warranty

Warranty	18 months
vvarranty	10 11011(13