

# 9422TD63

Operating mechanism, flange mounted, variable depth, 60A, 600 V, replacement fuse clips, for H, K, J, R fuses



## Main

Range	9422T
Product	Disconnect Switch
Disconnect Type	Non-fusible disconnect switch

## Complementary

Current Rating	60 A
Horsepower Rating	15 Hp 200 V AC 15 Hp 230 V AC 30 Hp 460 V AC 50 Hp 575 V AC 10 hp 250 V DC
Handle Type	Ordered separately

## Environment

Certifications	CSA UL Recognized
----------------	----------------------

## Ordering and shipping details

Category	21732-9422
Discount Schedule	CP1
GTIN	785901858461
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.50 in (11.43 cm)
Package 1 Width	6.00 in (15.24 cm)
Package 1 Length	6.70 in (17.018 cm)
Package 1 Weight	17.28 oz (489.88 g)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	18 months
----------	-----------