



### Main

Product or Component Type	Plug-in unit
Range of Product	I-Line
Circuit breaker type	L-Frame
Trip unit technology	Electronic, standard, MicroLogic 3.3, LI

### Complementary

Protection Type	Circuit breaker
Mounting Mode	Plug-in
[Ue] rated operational voltage	600 V AC
Line Rated Current	400 A
Number of Phases	3 phase
Poles description	3P
Interrupt Rating	25 KA 240 V AC 18 KA 480 V AC 14 kA 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Wiring configuration	4-wire (integral ground bus)
AWG gauge	AWG 2/0...500 kcmil 2 phase AWG 1/0...600 kcmil 2 neutral AWG 6...300 kcmil 1 ground
Depth	14.45 in (367 mm)
Height	17.40 in (442 mm)
Width	36.46 in (926 mm)

### Environment

Product Certifications	UL listed file E22182 CSA C22.2 No 27
Standards	UL 857

### Ordering and shipping details

Category	20188-PBLA C/B PLUGS
Discount Schedule	PE7
GTIN	785901944317
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	36.46 in (92.6 cm)
Package 1 Width	17.40 in (44.2 cm)
Package 1 Length	14.45 in (36.7 cm)
Package 1 Weight	120.00 lb(US) (54.431 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>