# Product data sheet Characteristics

# SC12L200S

Range of Product

Meter mains, Homeline, CSED, ringed socket, 200A, surface mount, no bypass





| Main                         |             |
|------------------------------|-------------|
| Product or Component<br>Type | Meter Mains |

Homeline

| Comp   | lemen    | tarv |
|--------|----------|------|
| COILIP | 10111011 | ·u·y |

| I                         |  |
|---------------------------|--|
| Line Rated Current        | 200 A  |
| Short-circuit current     | 10 kA  |
| Network number of phases  | 1  |
| Meter socket type         | Ringed   |
| Mounting                  | Surface  |
| Number of spaces          | 0  |
| Number of circuits        | 0  |
| Number of Tandem Breakers | 0  |
| Hub type                  | A-L  |
| Electrical connection     | Lugs line side<br>Lugs service ground  |
| Wire Size                 | AWG 4250 kcmil aluminium/copper)line side AWG 12AWG 2/0 aluminium/copper)service ground  |
| Tightening torque         | Main lugs 250 lb.in, AWG 6350 kcmil, aluminium/copper Lugs 250 lb.in, AWG 4300 kcmil, aluminium/copper Service ground 50 lb.in, AWG 14AWG 2/0, copper Service ground 50 lb.in, AWG 12AWG 2/0, aluminium Branch lugs 35 lb.in, AWG 6AWG 4, aluminium/copper Branch lugs 25 lb.in, AWG 8, aluminium/copper Branch lugs 20 lb.in, AWG 14AWG 10, copper Branch lugs 20 lb.in, AWG 12AWG 10, aluminium Cover 10 lb.in |
| Disconnect                | Service disconnect (ordered separately)  |
| Main Breaker Rating       | 200 A  |
| Service feed location     | OH<br>UG   |
| Bypass type               | No bypass  |
| Height                    | 29.50 in (749.30 mm)   |
| Width                     | 21.50 in (546.10 mm)   |
| Depth                     | 5.80 in (147.32 mm)  |
| Bus Rating                | 200.0 A  |
|                           |  |

#### **Environment**

| 2.17.101.1101.1        |           |
|------------------------|-----------|
| Product certifications | UL E-6294 |

## Ordering and shipping details

| 0 11 0            |                             |
|-------------------|-----------------------------|
| Category          | 00148-HOMELINE CSED DEVICES |
| Discount Schedule | DE3A                        |
| GTIN              | 785901377306                |
| Returnability     | Yes                         |
| Country of origin | MX                          |

## Packing Units

| 3 - 111                      |                            |
|------------------------------|----------------------------|
| Unit Type of Package 1       | PCE                        |
| Number of Units in Package 1 | 1                          |
| Package 1 Height             | 8.00 in (20.32 cm)         |
| Package 1 Width              | 22.00 in (55.88 cm)        |
| Package 1 Length             | 31.00 in (78.74 cm)        |
| Package 1 Weight             | 50.82 lb(US) (23.052 kg)   |
| Unit Type of Package 2       | PAL                        |
| Number of Units in Package 2 | 10                         |
| Package 2 Height             | 41.50 in (105.41 cm)       |
| Package 2 Width              | 40.00 in (101.6 cm)        |
| Package 2 Length             | 48.00 in (121.92 cm)       |
| Package 2 Weight             | 544.00 lb(US) (246.754 kg) |

## Offer Sustainability

| Sustainable offer status   | Green Premium product  WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |  |
|----------------------------|--|--|
| California proposition 65  |  |  |
| REACh Regulation           | ☑ REACh Declaration  |  |
| EU RoHS Directive          | Compliant EPEU RoHS Declaration  |  |
| Mercury free               | Yes  |  |
| China RoHS Regulation      | ☑ China RoHS Declaration   |  |
| RoHS exemption information | ₫Yes   |  |
| nvironmental Disclosure    |  |  |
|                            |  |  |

#### Contractual warranty

| Warranty | 18 months |  |
|----------|-----------|--|