QO250VH

Mini circuit breaker, QO, 50A, 2 pole, 120/240VAC, 22kA, plug in mount





Main	
Product	Miniature circuit-breaker
Range	QO
Current Rating	50 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated

Box lugs

Complementary

22 KA 120/240 V AC 50/60 Hz	
22 KA 120 V AC 50/60 HZ	
2	
AWG 8AWG 2 copper or aluminium	
49.56 lbf.in (5.6 N.m)	
3.11 in (79 mm)	
1.50 in (38 mm)	
2.91 in (74 mm)	
0.70 lb(US) (0.318 kg)	
	AWG 8AWG 2 copper or aluminium 49.56 lbf.in (5.6 N.m) 3.11 in (79 mm) 1.50 in (38 mm) 2.91 in (74 mm)

Electrical Connection

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00926-QO IND SPECIALTY CB
Discount Schedule	DE2A
GTIN	785901054962
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.70 in (9.398 cm)	
Package 1 Width	3.40 in (8.636 cm)	
Package 1 Length	1.60 in (4.064 cm)	
Package 1 Weight	11.20 oz (317.515 g)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months