



Overview

Lead time Usually in Stock



Main

| | |
|-----------------------|---------------------------------------|
| Main Input Voltage | 100 V 120 V |
| PDU Type | Basic |
| Main Output Voltage | 120 V |
| Input Connection Type | NEMA L5-30P |
| Number of rack unit | 1U |
| Cable length | 12 ft (3.66 m) |
| Number of cables | 1 |
| Provided Equipment | User Manual Rack Mounting brackets |

Physical

| | |
|---------------------|----------------------|
| Color | Black |
| Height | 1.73 in (4.4 cm) |
| Width | 17.60 in (44.7 cm) |
| Depth | 2.24 in (5.7 cm) |
| Net Weight | 5.51 lb(US) (2.5 kg) |
| Mounting Location | Front Rear |
| Mounting preference | No preference |
| Mounting Mode | Rack-mounted |
| Mounting position | Horizontal |

Input

| | |
|----------------------|------------|
| Line Rated Current | 24 A |
| Permissible voltage | 90...132 V |
| Max line current | 24 A |
| Input current limits | 30 A |
| Load Capacity | 2880 VA |
| Input Frequency | 50/60 Hz |

Output

| | |
|--------------------------------|---------------|
| Number of power socket outlets | 10 NEMA 5-20R |
|--------------------------------|---------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Conformance

| | |
|------------------------|-----------------------------|
| Product Certifications | cUL Listed[RETURN]UL Listed |
| Standards | UL 60950 |

Environmental

| | |
|---------------------------------------|----------------------------------|
| Ambient Air Temperature for Operation | 5...113 °F (-15...45 °C) |
| Relative Humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13...149 °F (-25...65 °C) |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |

Ordering and shipping details

| | |
|-------------------|---------------------------|
| Category | 11309-APC RESALE PRODUCTS |
| Discount Schedule | APC1 |
| GTIN | 731304192930 |
| Returnability | No |
| Country of origin | IN |

Packing Units

| | |
|------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.98 in (15.2 cm) |
| Package 1 Width | 6.97 in (17.7 cm) |
| Package 1 Length | 19.13 in (48.6 cm) |
| Package 1 Weight | 8.02 lb(US) (3.64 kg) |

Offer Sustainability

| | |
|-----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Lead free | Yes |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|