



Main

Range	Linergy
Product name	HK
Product or Component Type	Mounting plate
Poles description	3P
[I _{th}] conventional free air thermal current	25 A
I ² t on activation	200000 A ² .s
Number of cables	3 0.01 in ² (4 mm ²) 221 °F (105 °C)
Width	4.17 in (106 mm)
Height	7.48 in (190 mm)
Depth	2.48 in (63 mm)

Complementary

[Ui] rated insulation voltage	690 V IEC 60439-1
9 mm pitches	12
Net Weight	1.34 lb(US) (0.61 kg)

Environment

Standards	IEC 60439
Product Certifications	CSA[RETURN]LROS (Lloyds register of shipping)[RETURN]UL[RETURN]DNV

Ordering and shipping details

Category	22623-PANEL BUS (AK5)
Discount Schedule	I11
GTIN	3389110576962
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.87 in (7.300 cm)
Package 1 Width	4.92 in (12.500 cm)
Package 1 Length	8.07 in (20.500 cm)
Package 1 Weight	28.74 oz (814.900 g)
Unit Type of Package 2	S03
Number of Units in Package 2	9
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	17.74 lb(US) (8.048 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------