



Main

Range	ComPacT
Range of Product	ComPacT NSXm new generation
Device short name	MN
Product or Component Type	Voltage release
Device Application	Control
Voltage release type	Opening coil Undervoltage release
[Uc] control circuit voltage	110...130 V AC 50/60 Hz 125 V DC
Range compatibility	ComPacT ComPacT NSXm new generation ComPacT ComPacT NSXm PowerPact PowerPact B

Complementary

Operating threshold	0.35...0.7 x Un opening 0.85 x Un closing
Response time	< 50 ms
Auxiliary connection terminal	Pre-wired 0.00...0.00 in ² (0...0.8 mm ²) AWG 18)stranded copper
Wire stripping length	0.31 in (8 mm)
Cable length	3.28 ft (1 m)


Ordering and shipping details


Category	01136-PP-B FRAME ACCESSORIES
Discount Schedule	DE2
GTIN	3606485412931
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile

Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.