Product data sheet Characteristics

8538SDG14V02H30S

NEMA combination starter, Type S, 60A fusible disconnect, Size 2, 45A, 25HP at 600VAC, 3 phase, 3 pole, Motor Logic SSOLR, 120VAC coil, NEMA 1



Main

Product	Combination Starter
Туре	S
Control Circuit Type	Separate control circuit

Complementary

Complementary		
Control Circuit Voltage	110 V AC 50 Hz	
	120 V AC 60 Hz	
Starter Type	Non reversing	
Number of Poles	3P	
Horsepower Rating	25 Hp 460 V AC, 3 phase	
	25 hp 575 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	Without	
Thermal overload type	Solid state Motor Logic class 10/20	
Disconnect Type	Fusible disconnect switch H, 60 A	
NEMA size	2	

Environment

Englasura Tura	NEMA 1 rejected shoot stool with external reset
Enclosure Type	NEMA 1 painted sheet steel with external reset

Ordering and shipping details

Category	21213-8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901762577
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	37.84 lb(US) (17.164 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration

Contractual warranty

Warranty 18 months	
--------------------	--