

9065SFC20
Overload Relay, Motor Logic, solid state
overload relay, NEMA Size 00, 3 pole, 3A to
9A, 600VAC, separate mount



Main

Range of Product	Motor Logic
Thermal overload type	Solid state

Complementary

NEMA size	00
Phase	3 phase
Mounting Support	Mounting plate
[Ue] rated operational voltage	600 V AC
Height	2.69 in (68.3 mm)
Width	3.26 in (82.8 mm)
Depth	3.90 in (99.1 mm)
Net Weight	1.21 lb(US) (0.55 kg)

Ordering and shipping details

Category	21662-9065 SOLID STATE OVERLOAD RELAYS
Discount Schedule	CP1
GTIN	785901750031
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.31 in (13.5 cm)
Package 1 Width	5.39 in (13.7 cm)
Package 1 Length	6.10 in (15.5 cm)
Package 1 Weight	15.52 oz (440.0 g)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------