8536SBO2V02S

NEMA motor starter, Type S, nonreversing, Size 0, 18A, 5HP at 460VAC, 5kA SCCR, 3 phase, 3 pole, melting alloy, 120VAC coil, open



Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

Complementary		
NEMA Size	0	
Rated Current	18 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	6.81 in (172.96 mm)	
Width	3.50 in (88.90 mm)	
Depth	4.22 in (107.19 mm)	

Environment

Enclosure Type	Not rated (open device)	
Certifications	UL Listed[RETURN]CSA[RETURN]NEMA	

Ordering and shipping details

Category	21191-8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901864639
Returnability	Yes
Country of origin	MX

Packing Units

PCE
1
4.80 in (12.192 cm)
5.80 in (14.732 cm)
8.00 in (20.32 cm)
4.00 lb(US) (1.814 kg)
PAL
175
40.00 in (101.6 cm)
40.00 in (101.6 cm)
48.00 in (121.92 cm)
702.00 lb(US) (318.422 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☐ China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
	To monate

Approximate Dimensions

