

LC1D18F7TQ

IEC contactor, TeSys Deca, nonreversing, 18A, 10HP at 480VAC, up to 100kA SCCR, 3 phase, 3 NO, 110VAC 50/60Hz coil, bulk



Main

Range	TeSys TeSys Deca
Range of Product	TeSys Deca
Product or Component Type	Contactors
Device short name	LC1D
Contactors application	Resistive load Motor control
Utilisation category	AC-1 AC-3 AC-3e
Poles description	3P
[Ue] rated operational voltage	Power circuit <= 690 V AC 25...400 Hz
[Ie] rated operational current	32 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 18 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 18 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit
[Uc] control circuit voltage	110 V AC 50/60 Hz

Complementary

Motor power kW	10 KW at 500 V AC 50/60 Hz 10 KW at 660...690 V AC 50/60 Hz 4 KW at 220...230 V AC 50/60 Hz 7.5 KW at 380...400 V AC 50/60 Hz 9 kW at 415...440 V AC 50/60 Hz
Maximum Horse Power Rating	1 Hp at 115 V AC 50/60 Hz for 1 phase motors conforming to UL 1 Hp at 115 V AC 50/60 Hz for 1 phase motors conforming to CSA 10 Hp at 460/480 V AC 50/60 Hz for 3 phase motors conforming to CSA 10 Hp at 460/480 V AC 50/60 Hz for 3 phase motors conforming to UL 15 Hp at 575/600 V AC 50/60 Hz for 3 phase motors conforming to CSA 15 Hp at 575/600 V AC 50/60 Hz for 3 phase motors conforming to UL 5 Hp at 200/208 V AC 50/60 Hz for 3 phase motors conforming to CSA 5 Hp at 200/208 V AC 50/60 Hz for 3 phase motors conforming to UL 3 Hp at 230...240 V AC 50/60 Hz for 1 phase motors conforming to CSA 3 Hp at 230...240 V AC 50/60 Hz for 1 phase motors conforming to UL 5 Hp at 230...240 V AC 50/60 Hz for 3 phase motors conforming to CSA 5 hp at 230...240 V AC 50/60 Hz for 3 phase motors conforming to UL
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	With
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C)) for control circuit 32 A (at 140 °F (60 °C)) for power circuit
Irms rated making capacity	140 A AC for control circuit conforming to IEC 60947-5-1 300 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	300 kA at 440 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for control circuit conforming to IEC 60947-5-1 35 A at <= 690 V coordination type 2 for power circuit 50 A at <= 690 V coordination type 1 for power circuit
Average impedance	2.5 mOhm - Ith 32 A 50 Hz for power circuit

Power dissipation per pole	0.8 W AC-3 2.5 W AC-1 0.8 W AC-3e
[Ui] rated insulation voltage	Control circuit 600 V CSA[RETURN]Control circuit 600 V UL[RETURN]Power circuit 600 V CSA[RETURN]Power circuit 600 V UL[RETURN]Control circuit 690 V IEC 60947-4-1[RETURN]Power circuit 690 V IEC 60947-4-1
Overvoltage category	III
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical durability	15000000 cycles
Control circuit type	AC 50/60 Hz
Coil technology	Without built-in bidirectional peak limiting diode suppressor
Control circuit voltage limits	0.3...0.6 Uc 140 °F (60 °C) drop-out AC 50/60 Hz 0.8...1.1 Uc 140 °F (60 °C) operational AC 50 Hz 0.85...1.1 Uc 140 °F (60 °C) operational AC 60 Hz
Inrush power in VA	70 VA cos phi 0.75 (at 68 °F (20 °C))
Hold-in power consumption in VA	7 VA 50/60 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	2...3 W at 50/60 Hz for control circuit
Operating time	4...19 ms opening 12...22 ms closing
Maximum operating rate	3600 cyc/h 140 °F (60 °C)
Connections - terminals	Control circuit: screw clamp terminal 1 0.00...0.01 in ² (1...4 mm ²) - cable stiffness: solid without cable end Control circuit: screw clamp terminal 2 0.00...0.01 in ² (1...4 mm ²) - cable stiffness: solid without cable end Control circuit: screw clamp terminal 1 0.00...0.01 in ² (1...4 mm ²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 2 0.00...0.01 in ² (1...4 mm ²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 1 0.00...0.01 in ² (1...4 mm ²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminal 2 0.00...0.00 in ² (1...2.5 mm ²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminal 1 0.00...0.01 in ² (1.5...6 mm ²) - cable stiffness: solid without cable end Power circuit: screw clamp terminal 2 0.00...0.01 in ² (1.5...6 mm ²) - cable stiffness: solid without cable end Power circuit: screw clamp terminal 1 0.00...0.01 in ² (1...6 mm ²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminal 2 0.00...0.01 in ² (1...4 mm ²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminal 1 0.00...0.01 in ² (1.5...6 mm ²) - cable stiffness: flexible without cable end Power circuit: screw clamp terminal 2 0.00...0.01 in ² (1.5...6 mm ²) - cable stiffness: flexible without cable end
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) flat Ø 6 mm Control circuit 15.05 lbf.in (1.7 N.m) Philips No 2 Power circuit 15.05 lbf.in (1.7 N.m) flat Ø 6 mm Power circuit 15.05 lbf.in (1.7 N.m) Philips No 2 Control circuit 15.05 lbf.in (1.7 N.m) pozidriv No 2 Power circuit 15.05 lbf.in (1.7 N.m) pozidriv No 2
Auxiliary contact composition	1 NO + 1 NC
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 Ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
Mounting Support	Rail Plate

Environment

Standards	EN/IEC 60947-4-1 CSA C22.2 No 14 EN/IEC 60947-5-1 UL 508 IEC 60335-1
Product Certifications	CCC[RETURN]GOST[RETURN]JL[RETURN]JUL[RETURN]LROS (Lloyds register of shipping) [RETURN]DNV[RETURN]BV[RETURN]RINA[RETURN]CSA[RETURN]UKCA
IP degree of protection	IP2X IEC 60529 IP2X VDE 0106
Climatic withstand	IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat
Permissible ambient air temperature around the device	23...140 °F (-5...60 °C) -40...158 °F (-40...70 °C) at Uc
Operating altitude	9842.52 ft (3000 m) without derating
Fire resistance	1562 °F (850 °C) IEC 60695-2-1
Flame retardance	V1 conforming to UL 94
Mechanical robustness	Shocks contactor opened 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms) Vibrations contactor opened 2 Gn, 5...300 Hz) Vibrations contactor closed 4 Gn, 5...300 Hz)
Height	3.03 in (77 mm)
Width	1.77 in (45 mm)
Depth	3.39 in (86 mm)
Net Weight	7.28 lb(US) (3.3 kg)
Quantity per Set	Set of 10

Ordering and shipping details

Category	22354-CTR, TESYS D, OPEN, 9-38A AC
Discount Schedule	I12
GTIN	3389110123814
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.91 in (15.0 cm)
Package 1 Width	11.81 in (30.0 cm)
Package 1 Length	15.75 in (40.0 cm)
Package 1 Weight	11.29 oz (320.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	17.93 lb(US) (8.135 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	384
Package 3 Height	15.00 in (38.1 cm)
Package 3 Width	42.00 in (106.68 cm)
Package 3 Length	48.00 in (121.92 cm)
Package 3 Weight	342.00 lb(US) (155.128 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------