Product data sheet Characteristics

MD3304X

Motor disconnect switch, 3P, 30A, NEMA 1, 3, 3R, 4, 4X and 12 enclosure





Main	
Range	MD
Product	Motor Disconnect Switch
Current Rating	30 A
Horsepower Rating	7.5 Hp 220/240 V AC 20 Hp 440/480 V AC 25 hp 600 V AC
Enclosure Rating	NEMA 4X
Certifications	UL Listed

Complementary

Height	6.38 in (162.05 mm)	
Width	3.90 in (99.06 mm)	
Depth	4.37 in (111.00 mm)	
Product Weight	1.50 lb(US) (0.68 kg)	

Ordering and shipping details

Category	21734-TESYS VLS DISCONNECT SWITCHES
Discount Schedule	CP1
GTIN	3606480190223
Returnability	Yes
Country of origin	TN

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.92 in (12.5 cm)	
Package 1 Width	5.24 in (13.3 cm)	
Package 1 Length	7.20 in (18.3 cm)	
Package 1 Weight	24.32 oz (689.5 g)	
Unit Type of Package 2	S04	
Number of Units in Package 2	18	
Package 2 Height	11.81 in (30 cm)	
Package 2 Width	15.75 in (40 cm)	
Package 2 Length	23.62 in (60 cm)	
Package 2 Weight	29.19 lb(US) (13.24 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	72	
Package 3 Height	30.31 in (77.0 cm)	
Package 3 Width	31.50 in (80.0 cm)	
Package 3 Length	23.62 in (60.0 cm)	
Package 3 Weight	135.50 lb(US) (61.46 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Formaldehyde (gas), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months

Approximate Dimensions





