



Main

Product or Component Type	Tap box
Range of Product	Powerbus
Options	PM5350 meter

Complementary

Current Rating	400 A
Busbar Configuration	5B L1 + N + L2 + N + L3
Busbar Material	Silver plated copper: busbar
Integral Ground	50 percent capacity integral ground bus
Voltage Rating	480Y/277 V AC
Number of Phases	3 phase
Wiring configuration	4-wire (200 percent neutral)
Wire Gauge	AWG 1...600 kcmil 2 phase and neutral AWG 10...AWG 2/0 2 ground
Enclosure material	Painted aluminium Black

Environment

IP Degree of Protection	IP40
-------------------------	------

Ordering and shipping details

Category	20171-100A & 225A BUSWAY LENGTHS & FITTINGS
Discount Schedule	PE8
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	120.00 lb(US) (54.431 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes

China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information