

Product data sheet

Characteristics

37S3HNV

Low voltage transformer, non ventilated dry type, 3 phase, 37.5kVA, 240x480V primary, 120/240V secondary, Type 3R



Main

| | |
|------------------------|----------------------------|
| Product | Non-Ventilated Transformer |
| Enclosure Code | 18E |
| Insulation Temperature | 428 °F (220 °C) |
| Phase | 1 phase |
| Primary Voltage | 240 x 480 V |
| Power Rating | 37.5 kVA |
| Secondary Voltage | 120/240 V |
| Full Capacity Taps | 6 2.5 % 2+ 4- |
| Temperature Rise | 150 °C |
| Winding Material | Aluminium |

Ordering and shipping details

| | |
|-------------------|-------------------------------|
| Category | 16273-NON VENT NON RESIN LVGP |
| Discount Schedule | PE2 |
| GTIN | 785901350132 |
| Returnability | No |
| Country of origin | US |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 325.00 lb(US) (147.418 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|