

UATRS213B

Meter socket, ringless, 1 phase, 3 wire, 4 jaws,
Series A, no bypass, no jaw release



Main

Product or Component Type	Meter Socket
Meter socket type	Ringless
Hub type	A ACPA closing plate

Complementary

Meter socket rated current	200 A
Number of jaws	4 without jaw release
Bypass type	No bypass
Phase	1 phase
[Ue] rated operational voltage	600 V AC
Enclosure Material	Aluminum
Box number	5R
Electrical connection	Lugs 0.5" hex
Service feed location	UG OH
Wiring configuration	3-wire
Height	15.00 in (381.00 mm)
Width	11.00 in (279.40 mm)
Depth	4.38 in (111.25 mm)

Environment

Product Certifications	UL Listed
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	00039-METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	785901627791
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.60 in (14.224 cm)
Package 1 Width	11.80 in (29.972 cm)
Package 1 Length	15.70 in (39.878 cm)
Package 1 Weight	6.70 lb(US) (3.039 kg)
Unit Type of Package 2	PAL

Number of Units in Package 2	72
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	483.00 lb(US) (219.085 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	18 months
----------	-----------