LTM9CE180T

Motor Management, TeSys T, motor controller, 180° ethernet connection for shielded twisted pair cables





Main	
Range	TeSys
Product or Component Type	Ethernet TCP/IP communication adaptor
Accessory / separate part category	Communication accessory
Range compatibility	TeSys TeSys T LTMR motor controller TeSys TeSys T LTME extension module TeSys TeSys T LTMCU operator control unit

Complementary

Connections - terminals	1 x connector female RJ45 1 x connector male RJ45	
Direction change type	180°	
Quantity per Set	Set of 6	

Environment

LITVITOTITICITE		
Standards	EN 50173 class D	
	EIA-568 category 5	
	IEC 11801 class D	
	TIA-568 category 5	
Product Certifications	CSA 22-1[RETURN]UL	

Ordering and shipping details

0 11 0	
Category	22338-SOLID STATE OVERLOAD RELAYS
Discount Schedule	l12
GTIN	3389119412407
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.70 in (1.778 cm)
Package 1 Width	1.30 in (3.302 cm)
Package 1 Length	1.50 in (3.81 cm)
Package 1 Weight	0.80 oz (22.68 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	1.57 in (4 cm)
Package 2 Width	1.77 in (4.5 cm)
Package 2 Length	4.72 in (12 cm)
Package 2 Weight	5.57 oz (158 g)
Unit Type of Package 3	S02

Number of Units in Package 3	288	
Package 3 Height	5.91 in (15 cm)	
Package 3 Width	11.81 in (30 cm)	
Package 3 Length	15.75 in (40 cm)	
Package 3 Weight	17.72 lb(US) (8.039 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Contraction warranty		
Warranty	18 months	