## METSECTR30500

PowerLogic - Ropestyle current tranformer - 5000 A - d=96 mm - lead=2.4 m



#### Main Range PowerLogic **Product or Component** Current transducer Type Accessory / separate Measurement accessory part category Acti 9 Acti9 iEM3000 iEM3555[RETURN]Acti 9 Range compatibility Acti9 iEM3000 iEM3565[RETURN]PowerLogic PowerLogic EM4200 EM4235[RETURN]PowerLogic PowerLogic EM4200 EM4236[RETURN]PowerLogic PowerLogic EM3500 EM3502A[RETURN]PowerLogic PowerLogic EM3500 EM3550A[RETURN]PowerLogic

PowerLogic EM3500 EM3555A[RETURN]PowerLogic PowerLogic EM3500 EM3560A[RETURN]PowerLogic PowerLogic EM3500 EM3561A

Current transformer Flexible core type

### Complementary

Electrical connection	Flying lead 7.87 ft (2.4 m)600 V
Measurement current	505000 A
Network Frequency	50 Hz
Frequency measurement range	501500 Hz
Measurement accuracy	1 %
Installation category	IV
Pollution degree	2
Thickness	0.31 in (8 mm)
Height	Opened 11.81 in (300 mm)
Diameter	Closed 3.78 in (96 mm)

### Environment

Environment		
IP degree of protection	IP67	
Standards	EN 61010-2-032 UL 61010-2-032 UL 61010-1 EN 61010-1 ANSI/IEEE C57.13	
Product Certifications	UL Recognized[RETURN]CE[RETURN]cURus	
Relative humidity	095 %	
Ambient Air Temperature for Operation	5140 °F (-1560 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	

### Ordering and shipping details

Category	09661-POWERLOGIC BASIC CTS
Discount Schedule	PL1
GTIN	3606489421427
Returnability	Yes
Country of origin	IT

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.10 in (2.800 cm)
Package 1 Width	9.06 in (23.000 cm)
Package 1 Length	12.60 in (32.000 cm)
Package 1 Weight	5.57 oz (158.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	25
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	8.71 lb(US) (3.950 kg)

# Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.