HOM120PDF

Mini circuit breaker, Homeline, 20A, 1 pole, 120VAC, 10kA AIR, combo ARC/ground fault, plug on neutral, plug in, UL





Main Product Miniature circuit-breaker Range Homeline 20 A **Current Rating** Certifications **UL** Listed 120 V AC Voltage Rating Mounting Type Plug-in Number of Poles 1P Short Circuit Current 10 kA Rating **Number of Spaces** Circuit Breaker Type Combination ARC-fault and ground fault class A **HACR** rated Ratings **Electrical Connection** Clamp terminal for 2 cables Wire Size 1 x AWG 14...AWG 8 (aluminium/copper) 2 x AWG 14...AWG 10 (copper)

Complementary

Connections - Terminals	Plug-on neutral
Tightening torque	35.40 lbf.in (4.0 N.m) 0.000.01 in² (2.56 mm²) (AWG 14AWG 8)
Height	3.13 in (79.50 mm)
Width	1 in (25.40 mm)
Depth	2.98 in (75.69 mm)

Environment

Ambient Air Temperature for Operation	104 °E (40 °C)
Ambient Air Temperature for Oberation	104 °F (40 °C)

Ordering and shipping details

Category	06301-HOM SINGLE POLE ARC FAULT CIRCUIT BREAKER
Discount Schedule	DE3D
GTIN	785901978343
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.00 in (10.16 cm)	
Package 1 Width	5.00 in (12.7 cm)	
Package 1 Length	1.20 in (3.048 cm)	
Package 1 Weight	9.60 oz (272.155 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	40	
Package 2 Height	3.70 in (9.398 cm)	
Package 2 Width	20.80 in (52.832 cm)	

Package 2 Length	13.70 in (34.798 cm)	
Package 2 Weight	25.90 lb(US) (11.748 kg)	
Offer Sustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
Halogen content performance	Halogen free product	

Lifetime

Warranty